

# VLFT.EX28359 - Special System Water Control Valves, Deluge Type

## Special System Water Control Valves, Deluge Type

**GIACOMINI UNIVAL TESISAT ARMATURLERI SANAYI VE TICARET LTD.STI.**

EX28359

ISTANBUL ANADOLU TAKASI ORGANIZE SANAYI BOLGESI 1  
Sokak No 4. MERMERCILER CAD  
Tuzla Istanbul, 34953 Turkey

Pre-Action and Deluge (Wet and Dry Pilot) valve, Model UVPPD100, 4 in. size, vertical installation.

Pre-Action and Deluge (Wet and Dry Pilot) valve, Model UVPPD150, 6 in. size, vertical installation.

Model	Body Type	Nominal Pipe Size, NPS	End Configuration*	Max Rated Pressure, psig	Trim Configuration Type+	Installed Position
<b>Preaction sprinkler system</b>						
UVPR.5311-300	Globe	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	Class 300 - F by F F by G G by G	300	Double interlock w/ pneumatic-pneumatic actuation	V, H
					Double interlock w/ pneumatic-pneumatic actuation	

F - Flanged

G - Grooved


H - Horizontal orientation

V - Vertical orientation


\* End configurations are intended to be installed on systems not exceeding end configurations' working capabilities.

+ All trim configuration types shall include a manual release.

Height of pilot line above valve limited as shown in the installation instructions.

Trademark and/or tradename: 

Last Updated on 2022-10-24



UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."