

## VIZA.EX28842 - Fittings, Grooved and Plain End

## Fittings, Grooved and Plain End

GIACOMINI UNIVAL TESISAT ARMATURLERI SANAYI VE TICARET LTD.STI.

EX28842

ISTANBUL ANADOLU TAKASI ORGANIZE SANAYI BOLGESI 1

Sokak No 4. MERMERCILER CAD

Tuzla Istanbul, 34953 Turkey

## Grooved

Model	Type	Size In.	Rated Pressure (psig)
UV 20	90 Degree Elbow	1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3, 4, 5, 5-1/2 OD, 6, 6-1/2 OD, 8	500
UV 20	90 Degree Elbow	33.7mm, 76.1mm	500
UV 20	90 Degree Elbow	133.0mm, 267.4mm, 318.5mm	300
UV 20	90 Degree Elbow	14, 16, 18, 20, 24	300
UV 20	90 Degree Elbow	10	500
UV 20	90 Degree Elbow	12	500
UV 90C	90 Degree Elbow	114.3mm x 88.9mm x 33.7mm, 165.1mm x 88.9mm x 33.7mm	300
UV 22	90 Degree Short Elbow	2, 2-1/2, 3 OD, 3, 4, 5-1/2 OD, 6, 6-1/2 OD, 8	300
UV 22	90 Degree Short Elbow	108.0mm, 141.3mm	500
UV 22	90 Degree Short Elbow	114.3mm, 165.1mm	365
UV 22	90 Degree Short Elbow	159.0mm, 216.3mm	300
UV 21	90 Degree Reducing Elbow	88.9 x 76.1mm;	300
		114.3 x 76.1mm, 88.9mm;	
		165.1 x 114.3mm;	
		168.3 x 114.3mm	
UV 21	90 Degree Reducing Elbow	4x3	500
UV 24	90 Degree Reducing Elbow	1-1/4 x 1/2, 3/4, 1;	500
		1-1/2 x 1/2, 3/4, 1;	
		2 x 1/2, 3/4, 1;	
		2-1/2 x 1/2, 3/4, 1;	
		3 x 3/4, 1	

UV 25	11.25 Degree Elbow	42.4mm, 48.3mm, 60.3mm, 73mm, 76.1mm, 88.9mm, 114.3mm, 168.3mm 219.3mm	500
UV 25	11.25 Degree Elbow	108.0mm 139.7mm, 159.0mm, 165.1mm	300
UV 26	22.5 Degree Elbow	42.4mm, 48.3mm, 60.3mm, 73.0mm, 76.1mm, 88.9mm, 114.3mm, 168.3mm, 219.1mm	500
UV 26	22.5 Degree Elbow	108.0mm, 139.7mm, 159.0mm, 165.1mm	300
UV 28	45 Degree Elbow	1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3, 4, 5-1/4OD, 5, 6, 6-1/2 OD, 8, 10, 12	500
UV 28	45 Degree Elbow	33.7mm	500
UV 28	45 Degree Elbow	108.0mm, 139.7mm, 159.0mm, 216.3mm, 267.4mm, 318.5mm	300
UV 28	45 Degree Elbow	14, 16, 18, 20, 24	300
UV 30	Tee	1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3, 4, 5, 6, 6-1/2 OD, 8, 10, 12	500
UV 30	Tee	33.7mm, 76.1mm	500
UV 30	Tee	133.0mm, 139.7mm, 267.4mm	300
UV 30	Tee	14, 16, 18, 20, 24	300
UV 34	Reducing Tee	2 x 1-1/2;	500
		3 x 1, 1-1/2, 2, 2-1/2;	
		4 x 1, 2, 2-1/2, 3;	
		5 x 1-1/2, 2, 2-1/2, 3, 4;	
		6 x 2, 2-1/2, 3, 4, 5;	
		8 x 2, 2-1/2, 3, 4, 5, 6;	
		10 x 4	
		12 x 6	
UV 34	Reducing Tee	60.3 x 33.7mm, 48.3mm	500
		73.0 x 48.3mm, 60.3mm;	
		76.1 x 42.4mm, 48.3mm, 60.3mm;	
		88.9 x 42.4mm, 48.3mm, 60.3mm, 73.0mm	
		216.3 x 114.3mm	
UV 34	Reducing Tee	114.3 x 33.7mm, 60.3mm, 73.0mm, 88.9mm;	365
		141.3 x 88.9mm, 114.3mm;	
		168.3 x 60.3mm, 73.0mm, 88.9mm, 114.3mm, 141.3mm	
UV 34	Reducing Tee	14 x 8, 14 x 10, 14 x 2	300
UV 34	Reducing Tee	88.9 x 76.1mm;	300
		108.0 x 60.3mm, 73.0mm, 88.9mm;	
		114.3 x 48.3mm, 76.1mm;	

		133.0 x 60.3mm, 76.1mm, 108.0mm, 114.3mm;	
		139.7 x 48.3mm, 60.3mm, 76.1mm, 88.9mm, 114.3mm;	
		159.0 x 60.3mm, 76.1mm, 88.9mm, 108.0mm, 114.3mm, 133.0mm;	
		165.1 x 60.3mm, 76.1mm, 88.9mm, 114.3mm, 133.0mm, 139.7mm, 159.0mm;	
		168.3 x 76.1mm, 139.7mm;	
		216.3 x 165.1mm;	
		219.1 x 60.3mm, 76.1mm, 88.9mm, 108.0mm, 114.3mm, 133.0mm, 139.7mm, 141.3mm, 159.0mm, 165.1mm; 168.3mm	
		273.0 x 165.1mm, 168.3mm, 219.1mm;	
		323.9 x 165.1mm, 219.1mm, 273.0mm	
UV 31	Reducing Tee, Grooved	114.3mm x 88.9mm x 33.7mm, 165.1mm x 88.9mm x 33.7mm	300
UV 32	Reducing Tee, Grooved	114.3mm x 88.9mm x 33.7mm, 165.1mm x 88.9mm x 33.7mm	300
UV 33	Short Tee	2, 2-1/2, 3 OD, 3, 4, 5-1/2 OD, 6, 6-1/2 OD, 8	300
UV 33	Short Tee	108.0mm, 141.3mm	500
UV 33	Short Tee	114.3mm, 165.1mm	365
UV 33	Short Tee	159.0mm, 216.3mm	300
UV 37	Reducing Tee	60.3 x 33.7mm, 48.3mm;	500
		73.0 x 33.7mm, 42.4mm;	
		76.1 x 33.7mm, 42.4mm, 48.3mm, 60.3mm;	
		88.9 x 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm	
UV 37	Reducing Tee	108.0 x 60.3mm, 76.1mm, 88.9mm;	300
		114.3 x 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
		133.0 x 60.3mm, 76.1mm, 88.9mm;	
		139.7 x 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
		159.0 x 60.3mm, 76.1mm, 88.9mm;	
		165.1 x 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm, 114.3mm;	
		168.3 x 60.3mm, 76.1mm, 88.9mm	
UV 37	Reducing Tee	8 x 2	300
UV 37	Reducing Tee, Threaded	2 x 1-1/4;	500
		2-1/2 x 1-1/2, 2	
UV 40	Cross	1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3, 4, 5, 6, 6-1/2 OD, 8, 10, 12	500
UV 40	Cross	60.3mm, 73.0mm, 76.1mm, 88.9mm, 114.3mm, 141.3mm, 165.1mm	365
UV 40	Cross	108.0mm, 139.7mm, 159.0mm, 168.3mm, 219.1mm	300

UV 42	Reducing Cross	88.9 x 60.3mm	500
UV 42	Reducing Cross	114.3 x 60.3mm, 88.9mm;	300
		139.7 x 114.3mm;	
		159.0 x 108.0mm;	
		165.1 x 60.3mm, 76.1mm, 88.9mm, 114.3mm;	
		219.1 x 60.3mm, 114.3mm, 139.7mm, 159.0mm, 165.1mm	
UV 42	Reducing Cross	3OD x 2;	500
		6x2	
UV 44	Cross	114.3 x 33.7mm, 42.4mm, 48.3mm, 60.3mm;	300
		165.1 x 60.3mm	
UV 44	Reducing Cross	3x1-1/4	300
UV 44	Reducing Cross, Threaded	3OD x 2;	500
		3 x 1-1/2, 2;	
		4 x 3OD, 3;	
		6-1/2OD x 1-1/2	
UV 61	Grooved Eccentric Reducer	88.9 x 60.3mm;	500
		108.0 x 76.1mm, 88.9mm;	
		114.3 x 60.3mm, 88.9mm	
		168.3 x 141.3mm;	
		219.1 x 159.0mm, 165.1mm, 168.3mm	
UV 61	Grooved Eccentric Reducer	114.3 x 76.1mm;	300
		139.7 x 114.3mm;	
		159.0 x 108.0mm, 114.3mm;	
		165.1 x 88.9mm, 114.3mm, 139.7mm;	
		168.3 x 88.9mm, 114.3mm, 139.7mm;	
		219.1 x 114.3mm, 168.3mm;	
		273.1 x 219.1mm	
UV 61	Grooved Eccentric Reducer	14 x 8, 14 x 10, 14 x 12	300
UV 62	Grooved Eccentric Reducer With Male Thread	108.0 x 76.1mm	500
UV 62	Grooved Eccentric Reducer With Male Thread	114.3 x 76.1mm;	300
		139.7 x 88.9mm;	
		165.1 x 88.9mm	

UV 63	Grooved Concentric Reducer	2 x 3/4, 1, 1-1/4, 1-1/2;	500
		2-1/2 x 1, 1-1/4, 1-1/2, 2;	
		3 x 3/4, 1, 1-1/2, 2, 2-1/2;	
		4 x 1, 1-1/2, 2, 2-1/2, 3;	
		5 x 3, 4;	
		6 x 1, 2, 2-1/2, 3, 4, 5;	
		8 x 2-1/2, 3, 4, 5, 6	
		10 x 6, 8;	
		12 x 6, 8, 10	
UV 63	Grooved Concentric Reducer	42.4 x 33.7mm;	500
		48.3 x 33.7mm, 42.4mm;	
		76.1 x 33.7mm, 42.4mm, 48.3mm, 60.3mm;	
		88.9 x 76.1mm;	
		108.0 x 60.3mm, 73.0mm, 88.9mm;	
		141.3 x 76.1mm;	
		165.1 x 108mm;	
		219.1 x 108mm	
UV 63	Grooved Concentric Reducer	88.9 x 42.4mm;	365
		133.0 x 108.0mm, 114.3mm;	
		139.7 x 60.3mm;	
		141.3 x 88.9mm, 114.3mm	
UV 63	Grooved Concentric Reducer	108.0 x 76.1mm;	300
		114.3 x 42.4mm, 76.1mm;	
		139.7 x 76.1mm, 88.9mm, 114.3mm;	
		141.3 x 73.0mm;	
		159.0 x 60.3mm, 76.1mm, 88.9mm, 108.0mm, 114.3mm, 133.0mm;	
		165.1 x 60.3mm, 76.1mm, 88.9mm, 114.3mm, 139.7mm;	
		168.3 x 76.1mm, 139.7mm;	
		216.3 x 114.3mm, 165.1mm;	
		219.1 x 108.0mm, 139.7mm, 159.0mm, 165.1mm;	
		273.0 x 159.0mm, 165.1mm,;	

UV 63	Grooved Concentric Reducer	14 x 8, 14 x 10, 14 x 12	300
UV 65	Concentric Reducer - FNPT	1 x 1/2;	500
		2 x 1/2, 3/4, 1, 1-1/4, 1-1/2;	
		2-1/2 x 1, 1-1/4, 1-1/2, 2;	
		3 x 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2;	
		4 x 1, 1-1/2, 2, 2-1/2, 3;	
		5 x 3, 4;	
		6 x 1, 2, 2-1/2, 3, 4, 5;	
		8 x 2-1/2, 3, 4, 5, 6	
UV 65	Concentric Reducer With Female Thread	76.1 x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm	500
		139.7 x 60.3mm, 88.9mm;	
		159.0 x 76.1mm	
UV 65	Concentric Reducer With Female Thread	88.9 x 21.3mm;	365
		133.0 x 48.3mm, 76.1mm;	
		139.7 x 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm, 114.3mm;	
		141.3 x 88.9mm, 114.3mm	
UV 65	Concentric Reducer With Female Thread	88.9 x 42.4mm, 76.1mm;	300
		108.0 x 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1 mm, 88.9mm;	
		114.3 x 21.3 mm, 26.9mm, 42.4mm, 76.1 mm;	
		159.0 x 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 88.9mm, 114.3mm;	
		165.1 x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm, 114.3mm;	
		219.1 x 48.3mm, 60.3mm, 76.1mm	
UV 67	Concentric Reducer - MNPT	2 x 3/4, 1, 1-1/4, 1-1/2;	500
		2-1/2 x 1, 1-1/4, 1-1/2, 2;	
		3 x 3/4, 1, 1-1/2, 2, 2-1/2;	
		4 x 1, 1-1/2, 2, 2-1/2, 3;	
		5 x 3, 4;	
		6 x 1, 2, 2-1/2, 3, 4, 5;	
		8 x 2-1/2, 3, 4, 5, 6	

UV 67	Concentric Reducer - MNPT	76.1 x 60.3mm	500
		88.9 x 76.1mm	
UV 67	Concentric Reducer - FNPT	2 x 1, 1-1/4, 1-1/2; 2-1/2 x 1, 1-1/4, 1-1/2; 3 x 1-1/2, 2, 2-1/2; 4 x 1, 1-1/2, 2-1/2, 3	500
UV 71	Cap	1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3, 4, 5, 5-1/2 OD, 6, 6-1/2 OD, 8, 10, 12	500
UV 71	Cap	33.7mm	500
UV 71	Cap	108.0mm, 133.0mm, 139.7mm, 159.0mm, 216.3mm	300
UV 71	Cap	76.1 x 48.3mm	500
		168.3 x 21.3mm, 60.3mm;	
		219.1 x 33.7mm	
UV 71	Cap	88.9 x 60.3mm;	365
		114.3 x 60.3mm;	
		139.7 x 60.3mm;	
		165.1 x 60.3mm	
UV 71	Cap	88.9 x 21.3mm, 33,7mm, 48.3mm;	300
		114.3 x 21.3mm, 33.7mm, 48.3mm;	
		165.1 x 21.3mm, 33.7mm;	
		168.3 x 48.3mm	
UV 71	Cap	14	300
UV 72	Cap	2-1/2 x 1;	500
		3OD x 1;	
		4 x 1	
UV 72	Cap	88.9 x 48.3mm, 60.3mm;	365
		114.3 x 48.3mm, 60.3mm;	
		139.7 x 48.3mm, 60.3mm;	
		165.1 x 48.3mm;	
		168.3 x 48.3mm, 60.3mm	
UV 72	Cap	219.1 x 48.3mm, 60.3mm	300
UV 81	Flange Adapter	2, 2-1/2, 3 OD, 3, 4, 5, 5-1/2 OD, 6, 6-1/2 OD, 8	300
UV 81	Flange Adapter	10, 12	225
UV 81	Flange Adapter	33.7mm, 42.4mm, 48.3mm, 60.3mm, 73.0mm, 76.1mm, 88.9mm, 108.0mm, 114.3mm, 133.0mm, 139.7mm, 141.3mm, 159.0mm, 165.1mm, 168.3mm	300

UV 81	Flange Adapter	219.1mm, 273.1mm, 323.9mm	225
UV 94	Flange Adapter	2, 3OD, 3, 8, 10	300
UV 93	Flange Adapter	6-1/2OD	300
UV 83	Flange Adapter	2, 4, 8, 10, 14, 16, 18, 20, 24	300
UV 84	Flange Adapter	159.0mm	300
UV 84	Flange Adapter	14, 16	300
UV 84	Flange Adapter	4-1/4OD(108mm), 4, 6-1/2OD(165.1mm), 8	365
UV 95	Flange Adapter	219.1mm, 273.0mm	225
UV 23	90 Degree Short Elbow	3, 4-1/4OD, 4, 5-1/4OD, 5-1/2OD, 6-1/4OD, 6-1/2OD, 6, 10, 12	300
UV 27	22.5 Degree Short Elbow	4, 6-1/4OD, 6-1/2OD	300
UV 29	45 Degree Short Elbow	3, 4-1/4OD, 4, 5-1/2OD, 6-1/4OD, 6-1/2OD, 6, 8, 10	300
UV 35	Short Tee	3, 4-1/4OD, 4, 5-1/4OD, 5-1/2OD, 6-1/4OD, 6-1/2OD, 6, 8, 10, 12	300
UV 34	Reducing Tee	10 x 4	500
UV 36	Short Reducing Tee, Grooved	3 x 2-1/2, 3OD;	300
		4 x 2, 2-1/2, 3;	
		5-1/2OD x 4;	
		5 x 4;	
		6-1/4OD x 3, 4-1/4OD, 4, 5-1/4OD;	
		6-1/2OD x 2, 3OD, 3, 4, 5-1/2OD;	
		6 x 2, 2-1/2, 3OD, 3, 4, 5-1/2OD, 5;	
		8 x 3OD, 3, 4, 5-1/2OD, 6-1/4OD, 6-1/2OD, 6;	
		10 x 6-1/4OD, 6-1/2OD, 6, 8;	
		12 x 4, 6-1/4OD, 6-1/2OD, 8, 10	
UV 38	Short Reducing Tee, Threaded	2 x 1, 1-1/2;	300
		2-1/2 x 1-1/2, 2;	
		3OD x 1-1/2, 2;	
		3 x 1, 1-1/2, 2;	
		4-1/4OD x 3OD;	
		4 x 2, 3OD, 3;	
		6-1/2OD x 2, 3OD, 3, 4;	
		6 x 2, 3OD, 3, 4;	
		8 x 3OD, 4	



		6-1/2OD x 2, 3OD, 3, 4;	
		6 x 2, 3OD, 3, 4;	
		8 x 3OD, 4	
UV 41	Short Cross	6-1/4OD, 6-1/2OD, 6, 8	300
UV 43	Short Reducing Cross, Grooved	6-1/2OD x 4;	300
		6 x 4;	
		8 x 6-1/2OD, 6	
UV 45	Short Reducing Cross, Threaded	6-1/2OD x 3	300
UV 66	Short Concentric Reducer With Female Thread	3OD x 2;	300
		3 x 2, 3OD;	
		4-1/4OD x 3OD, 3;	
		4 x 1-1/2, 2, 3OD, 3;	
		6-1/2OD x 2, 3OD, 3, 4;	
		8 x 1	
UV 64	Short Grooved Concentric Reducer	4 x 3OD, 3;	300
		5-1/2OD x 4;	
		6-1/4OD x 4-1/4OD, 4;	
		6-1/2OD x 3, 4, 5-1/2OD;	
		6 x 4, 5-1/2OD;	
		8 x 4, 5-1/4OD, 6-1/2OD;	
		10 x 4, 8;	
		12 x 4, 6-1/4OD, 6-1/2OD	
UV 60	PAINTED GROOVED x FEMALE ADAPTER	2, 2-1/2, 3, 4	500

Last Updated on 2022-07-26

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL 认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“©2022 UL LLC.”

# VIZM.EX28843 - Fittings, Rubber Gasketed

## Fittings, Rubber Gasketed

**GIACOMINI UNIVAL TESISAT ARMATURLERI SANAYI VE TICARET LTD.STI.**

EX28843

ISTANBUL ANADOLU TAKASI ORGANIZE SANAYI BOLGESI 1

Sokak No 4. MERMERCILER CAD

Tuzla Istanbul, 34953 Turkey

### Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
UV 15	Rolled	10	1-1/4, 1-1/2, 2-1/2	500
UV 15	Rolled	10	2, 3, 4, 5, 6	500
UV 15	Rolled	10	8	500
UV 15	Rolled	10	10, 12	500
UV 15	Rolled	1387-10	3 OD, 6-1/2 OD	300
UV 15	Rolled	1387-M	5-1/2 OD	450
UV 15	Rolled, Cut	40	1-1/4, 1-1/2	500
UV 15	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6	500
UV 15	Rolled, Cut	40	8	500
UV 15	Rolled, Cut	40	10, 12	500
UV 15	Rolled	ASME B36.10M-10	14, 16, 18, 20, 24	300
UV 15	Rolled, Cut	ASME B36.10M-40	14, 16, 18, 20, 24	300
UV 15	Rolled, Cut	1387-40	3 OD, 6-1/2 OD	300
UV 15	Rolled, Cut	1387-H	5-1/2 OD	450

UV 15	Rolled, Cut	4200	33.7 / 3.2mm, 108.0 / 4.0mm	500
-------	-------------	------	-----------------------------	-----

UV 15	Rolled, Cut	4200	133.0 / 5.4mm, 159.0 / 4.0mm	300
UV 15	Rolled, Cut	3454-20	267.4 / 6.4mm, 318.5 / 6.4mm	225
UV 15	Rolled, Cut	4200	355.6 / 6.3mm, 406.4 / 6.3mm	175
UV 16	Rolled	10	4	365
UV 16	Rolled	10	3, 6, 8, 10	300
UV 16	Rolled	40	3, 4, 6, 8, 10	300
UV 16	Rolled	1387-M	3 OD, 5-1/2 OD, 6-1/2 OD	300
UV 16	Rolled	1387-H	3 OD, 5-1/2 OD, 6-1/2 OD	300
UV 16	Rolled, Cut	4200	108.0 / 4.0mm, 141.3 / 6.3mm, 159.0 / 4.0mm	300
UV 16	Rolled, Cut	3454-20	216.3 / 6.4mm	300
UV 19	Rolled, Cut	4200 E	1-1/4, 1-1/2, 2	500
UV 19	Rolled, Cut	4200 E	3, 4	300
UV 19	Rolled, Cut	4200 E	76.1mm	300
UV 19	Rolled, Cut	4200 D	139.7mm	300
UV 19	Rolled, Cut	1387-M	165.1mm	300
UV 19	Rolled, Cut	3454-20	216.3mm	300
UV 19	Rolled	10	2-1/2	500
UV 19	Rolled	10	6, 8, 10	300
UV 19	Rolled, Cut	40	2-1/2	500
UV 19	Rolled, Cut	40	6, 8, 10	300
UV 18	Rolled	10	1-1/4, 1-1/2, 3, 4, 8, 10	300
UV 18	Rolled, Cut	40	1-1/4, 1-1/2, 3, 4, 8, 10	300
UV 18	Rolled	GB/T 21835	3OD(4.5mm), 4-1/4OD(5.4mm) 5-1/4OD(5.6mm), 5-1/2OD(5.6mm) 6-1/4OD(6.3mm), 6-1/2OD(6.3mm)	300

UV 18	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 8, 10	363
-------	--------	----	-------------------------------------	-----

UV 18	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 8, 10	363
UV 18	Rolled, Cut	GB/T 21835	3OD(4.5mm), 4-1/4OD(5.4mm), 5-1/4OD(5.6mm), 5-1/2OD(5.6mm), 6-1/4OD(6.3mm), 6-1/2OD(6.3mm)	363
UV 17	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	750
UV 17	Rolled, cut	40	2, 2-1/2, 3, 4, 5, 6, 8	750
UV 17	Rolled, cut	T21835	3OD(5.0mm), 5-1/2OD (6.3mm), 6-1/2OD(7.1mm)	750
UV 17	Rolled	10	10, 12	500
UV 17	Rolled, cut	40	10, 12	500
UV 09	Rolled	10	4, 8	300
UV 09	Rolled, Cut	40	4, 8	300
UV 09	Rolled	GB/T 21835	6-1/2OD(6.3mm)	300
UV 87	Rolled	10	2, 3, 4	300
UV 87	Rolled, Cut	40	2, 3, 4	300
UV 87	Rolled, Cut	4200	3OD(4.5mm), 5-1/2OD(5mm)	300
UV 87	Rolled, Cut	10255-M	6-1/2OD	300
UV 87	Rolled, Cut	3454-20	216.3mm	300
UV 87	Rolled, Cut	3454-40	216.3mm	300
UV 88	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
UV 88	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
UV 88	Rolled, Cut	EN 10255-H	76.1mm(4.5mm), 139.7mm(5.4mm), 165.1mm(5.4mm)	300
UV 88	Rolled, Cut	T21835	3OD(4.5mm), 5-1/2OD(5.6mm), 6-1/2OD(6.3mm)	300
UV 88	Rolled, Cut	3454-40	216.3mm	300
UV 88	Rolled, Cut	3452-SGP	216.3mm	300

### Flexible coupling

Model	Groove	Pipe	Size (in.)	Rated Pressure
-------	--------	------	------------	----------------

	Type			(psig)
UV 11	Rolled	10	2, 2-1/2, 3, 4, 5	300
UV 11	Rolled	10	1-1/4, 1-1/2, 6, 8	500
UV 11	Rolled	1387-10	3 OD, 6-1/2 OD	300
UV 11	Rolled	1387-M	5-1/2 OD	450
UV 11	Rolled	1387-M, 10	3 OD x 1-1/2, 2; 3 x 3 OD; 4 x 3 OD; 8 x 6-1/2 OD	300
UV 11	Rolled	EN10255-M	88.9mm x 60.3mm; 114.3mm x 60.3mm, 88.9mm; 165.1mm x 114.3mm;	360
UV 11	Rolled, Cut	40	2, 2-1/2, 3, 4, 5	300
UV 11	Rolled, Cut	40	1-1/4, 1-1/2, 6, 8	500
UV 11	Rolled, Cut	1387-40	3 OD, 6-1/2 OD	300
UV 11	Rolled	ASME B36.10M-10	14, 16, 18, 20, 24	300
UV 11	Rolled, Cut	ASME B36.10M-40	14, 16, 18, 20, 24	300
UV 11	Rolled, Cut	1387-H	5-1/2 OD	450
UV 11	Rolled, Cut	1387-H, 40	3 OD x 1-1/2, 2; 3 x 3 OD; 4 x 3 OD; 8 x 6-1/2 OD	300
UV 11	Rolled	EN10255-H	88.9mm x 60.3mm; 114.3mm x 60.3mm, 88.9mm; 165.1mm x 114.3mm;	360
UV 11	Rolled	10	2-1/2 x 2; 3 x 2, 2-1/2; 4 x 2, 2-1/2, 3; 5 x 4; 6 x 4, 5; 8 x 6	360
UV 11	Rolled, cut	40	2-1/2 x 2; 3 x 2, 2-1/2; 4 x 2, 2-1/2, 3; 5 x 4; 6 x 4, 5; 8 x 6	360
UV 11	Rolled, Cut	4200	33.7 / 3.2mm, 108.0 / 4.0mm	500
UV 11	Rolled, Cut	4200	133.0 / 5.4mm, 159.0 / 4.0mm	300

UV 11	Rolled, Cut	4200	73.0 / 3.2 x 33.7 / 3.2mm; 76.1 / 3.6 x 33.7 / 3.2mm; 88.9 / 3.2 x 33.7 / 3.2mm; 114.3 / 3.6 x 33.7 / 3.2mm; 168.3 / 4.0 x 88.9 / 3.2mm	300
UV 11	Rolled, cut	4200	60.3mm(4.0mm) x 33.7(3.2mm), 48.3mm(4.0mm); 219.1mm(5.0mm) x 168.3mm(5.0mm)	360
UV 11	Rolled, Cut	4200	273.0 / 6.3mm, 323.9 / 6.3mm	500
UV 10	Rolled, Cut	4200	60.3 / 3.2mm, 73.0 / 3.2mm, 76.1 / 3.6mm, 88.9 / 3.2mm, 114.3 / 3.6mm, 141.3 / 6.3mm	750
UV 10	Rolled, Cut	4200	168.3 / 4.0mm, 219.1 / 5.0mm	750
UV 10	Rolled, Cut	EN10255-M	139.7mm, 165.1 / 5.0mm	750
UV 10	Rolled	10	12	500
UV 10	Rolled, Cut	40	12	500
UV 10	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	750
UV 10	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8	750
UV 13	Rolled	10	2, 2-1/2, 4, 6, 8, 10	300
UV 13	Rolled, Cut	40	2, 2-1/2, 4, 6, 8, 10	300
UV 13	Rolled Cut	T21835	6-1/2OD(6.3mm)	300
UV 13	Rolled Cut	EN 10255 H	139.7mm(5.4mm)	300
C1X	Rolled	10	2-1/2, 4, 6, 8, 10	300
C1X	Rolled, Cut	40	2-1/2, 4, 6, 8, 10	300
C1X	Rolled Cut	T21835	6-1/2OD(6.3mm)	300
UV 11	Rolled	10	6 x 6-1/2OD(6.3mm)	300
UV 11	Rolled, Cut	40	6 x 6-1/2OD(6.3mm)	300
UV 11	Rolled	GB/T 21835	6-1/2OD(6.3mm) x 3;	300
UV 11	Rolled, Cut	GB/T 21835	3OD(4.5mm) x 2-1/2(4.5mm)	300

UV 89	Rolled	10	2, 3, 4	300
-------	--------	----	---------	-----

UV 89	Rolled Cut	40	2, 3, 4	300
UV 89	Rolled Cut	4200	3OD(4.5mm), 5-1/2OD(5mm), 6-1/2OD(6.3mm)	300
UV 89	Rolled Cut	3452	216.3 mm	300
UV 90	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
UV 90	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
UV 90	Rolled, Cut	EN 10255-H	76.1mm(4.5mm), 139.7mm(5.4mm), 165.1mm(5.4mm)	300
UV 90	Rolled, Cut	T21835	3OD(4.5mm), 5-1/2OD(5.6mm), 6-1/2OD(6.3mm)	300
UV 90	Rolled, Cut	3454-40	216.3mm	300
UV 90	Rolled, Cut	3452-SGP	216.3mm	300
UV 12	Rolled	10	2, 3, 4, 6, 10	300
UV 12	Rolled Cut	40	2, 3, 4, 6, 10	300
UV 12	Rolled Cut	GB/T 21835	5-1/2OD(5.6mm), 6-1/2OD(6.3mm)	300
UV 12	Rolled	10	6 x 4	300
UV 12	Rolled Cut	40	6 x 4	300
UV 12	Rolled	ASME B36.10M-10	16	300
UV 12	Rolled, Cut	ASME B36.10M-40	16	300
UV 12	Rolled, cut	EN 10255 H	76.1mm(4.5mm)	300

**Flange adapter**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
UV 80	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	300
UV 80	Rolled	1387-10	3OD, 6-1/2 OD	300
UV 80	Rolled	10	10, 12	225
UV 80	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8	300

UV 80	Rolled, Cut	1387-40	3OD, 6-1/2 OD	300
-------	-------------	---------	---------------	-----

UV 80	Rolled, Cut	40	10, 12	225
UV 80	Rolled, Cut	4200	48.3 / 4.0mm, 108.0 / 3.6mm	300
UV 80	Rolled, Cut	4200	133.0 / 3.2mm, 139.7 / 3.6mm, 159.0 / 4.5mm	225
UV 80	Rolled	ASME B36.10M-10	14	300
UV 80	Rolled, Cut	ASME B36.10M-40	14	300
UV 91	Rolled	10	2, 2-1/2, 3, 4	300
UV 91	Rolled	10	5	250
UV 91	Rolled, cut	40	5	250
UV 91	Rolled	ASME B36.10M-10	14	300
UV 91	Rolled, Cut	ASME B36.10M-40	14	300
UV 91	Rolled, Cut	4200	219.1 / 5.0mm, 273.0 / 6.3mm, 323.9 / 6.3mm	250
UV 92	Rolled	10	3, 4, 6, 8	300
UV 92	Rolled, Cut	40	3, 4, 6, 8	300
UV 96	Rolled, Cut	1387-M	165.1mm	225
UV 82	Rolled	10	2, 3, 4, 8	300
UV 82	Rolled, Cut	40	2, 3, 4, 8	300
UV 82	Rolled	GB/T 21835	6-1/2OD(6.3mm)	300

**Side outlet**

Model	Outlet Type	Pipe	Size (in.)	Rated Pressure (psig)
UV 51	Grooved	10, 40	3 x 2;	300
			4 x 2, 3OD;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 2, 3OD;	
			10 x 3OD, 3	
UV 51	Grooved	1387-M, 1387-H	3 OD x 1-1/4, 1-1/2;	300
			5-1/2 OD x 2, 2-1/2, 3;	
			6-1/2 OD x 2, 2-1/2, 3	

UV 51	Grooved	10, 40	2-1/2 x 1; 3 x 1;	300
-------	---------	--------	----------------------	-----



			4 x 1;	
			8 x 76.1mm, 3, 108.0mm, 4	
UV 51	Grooved	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2; 4 x 1-1/4, 1-1/2, 2-1/2, 3; 6 x 1-1/2, 2-1/2, 3, 4; 8 x 2, 2-1/2	400
UV 51	Grooved	4200	76.1 / 3.6 x 33.7 / 3.2mm;	300
			133.0 / 3.2mm x 88.9mm;	
			139.7 / 3.6mm x 42.4mm, 48.3mm;	
			273.0 / 6.3 x 108.0 / 4.0mm, 114.3 / 3.6mm	
UV 51	Grooved	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 108.0mm, 114.3mm	
UV 51	Grooved	1387-M	165.1 x 114.3mm	225
UV 51	Grooved	GB/T 21835	6-1/4OD(6.3mm) x 2	300
UV 52	Grooved	10, 40	3 x 1, 1-1/4, 1-1/2, 2;	300
			4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			5 x 2;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			8 x 2, 2-1/2, 76.1mm, 3, 108.0mm, 4	
UV 52	Grooved	10, 40	6 x 4	225
UV 52	Grooved	10, 40	5 x 2-1/2, 3	400
UV 52	Grooved	4200	133.0 / 3.2mm x 88.9mm;	300
			139.7 / 3.6mm x 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	
UV 52	Grooved	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 108.0mm, 114.3mm	
UV 52	Grooved	1387-M	165.1 x 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	300
UV 52	Grooved	1387-M	165.1 x 108.0mm, 114.3mm	225
UV 52	Grooved	GB/T 21835	6-1/4OD(6.3mm) x 3	300
UV 53	Threaded	10, 40	3 x 1, 1-1/4	500
UV 53	Threaded	10, 40	1 x 1/2;	300
			1-1/4 x 1/2, 3/4;	
			1-1/2 x 1/2, 3/4	

			2 x 1/2, 3/4	
			2 1/2 x 1/2, 3/4	
			3 x 2;	
			4 x 2;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 2, 3	
UV 53	Threaded	1387-M, 1387-H	3 OD x 1, 1-1/4, 1-1/2;	300
			5-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	
UV 53	Threaded	10, 40	8 x 1, 1-1/4, 1-1/2, 2-1/2, 76.1mm, 3, 4	300
UV 53	Threaded	10, 40	2 x 1, 1-1/4, 1-1/2; 2-1/2 x 1, 1-1/4, 1-1/2; 3 x 1/2, 3/4, 1-1/2; 4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2-1/2, 3; 6 x 1-1/2, 2-1/2, 4; 8 x 2	400
UV 53	Threaded	4200	273.0 / 6.3 x 114.3 / 3.6mm	225
UV 53	Threaded	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 114.3mm	
UV 53	Threaded	4200	76.1 / 3.6 x 21.3 / 2.8mm, 26.9 / 2.9mm;	300
			108.0 / 3.6mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm;	
			133.0 / 3.2mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			139.7 / 3.6mm x 21.3mm, 26.9mm;	
			159.0 / 4.5mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			273.0 x 48.3 / 4.0mm, 60.3 / 3.2mm, 76.1 / 3.6mm, 88.9 / 3.2mm	
UV 53	Threaded	4200	60.3mm(3.2mm) x 21.3mm(2.8mm), 26.9mm(2.9mm); 73.0mm(3.2mm) x 21.3mm(2.8mm), 26.9mm(2.9mm);	400
UV 53	Threaded	1387-M	165.1 x 21.3mm, 26.9mm	300
UV 53	Threaded	1387-M	165.1 x 114.3mm	225
UV 54	Threaded	10, 40	3 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2;	300
			4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			5 x 2;	

			6 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			8 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3, 4	
UV 54	Threaded	10, 40	6 x 4	225
UV 54	Threaded	4200	108.0 / 3.6mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm;	300
			133.0 / 3.2mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			139.7 / 3.6mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			159.0 / 4.5mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	
UV 54	Threaded	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 114.3mm	
UV 54	Threaded	1387-M	165.1 x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	300
UV 54	Threaded	1387-M	165.1 x 114.3mm	225
UV 54	Threaded	10, 40	5 x 1-1/2	400
UV 55	Threaded	10, 40	2-1/2 x 1, 1-1/2; 3 x 1, 1-1/4, 1-1/2, 2; 4 x 1, 1-1/4, 1-1/2, 2, 3OD	300
UV 55	Threaded	GB/T 21835	3OD(4.5mm) x 1, 1-1/4	300
UV 50	Threaded	4200	42.4 / 3.6 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm;	300
			48.3 / 4.0 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm;	
			60.3 / 3.2 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm;	
			73.0 / 3.2 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm;	
			76.1 / 3.6 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm;	
			88.9 / 3.2 x 33.7 / 3.2mm	
UV 56	Grooved	10, 40	2 x 1-1/4, 1-1/2;	300
			2-1/2 x 1-1/4, 1-1/2;	
			3 x 1-1/4, 1-1/2, 2;	
			4 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	
UV 56	Grooved	1387-M, 1387-H	3 OD x 1-1/4, 1-1/2;	300
			5-1/2 OD x 2, 2-1/2, 3;	

			6-1/2 OD x 2, 2-1/2, 3	
--	--	--	------------------------	--

UV 58	Threaded	10, 40	2 x 1, 1-1/4, 1-1/2;	300
			2-1/2 x 1, 1-1/4, 1-1/2;	
			3 x 1, 1-1/4, 1-1/2, 2;	
			4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	
UV 58	Threaded	1387-M, 1387-H	3 OD x 1, 1-1/4, 1-1/2;	300
			5-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	
UV 85	Threaded and Grooved	10, 40	2 x 1-1/4, 1-1/2;	300
			2-1/2 x 1-1/4, 1-1/2;	
			3 x 1-1/4, 1-1/2, 2;	
			4 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	
UV 85	Threaded and Grooved	1387-M, 1387-H	3 OD x 1-1/4, 1-1/2;	300
			5-1/2 OD x 2, 2-1/2, 3;	
			6-1/2 OD x 2, 2-1/2, 3	

The fittings are suitable for use in dry pipe systems for temperatures to -40 F with the exception of Model UV 19, UV 18, UV 09, UV 13, 321E, UV 89, UV 87.

Model UV 53, UV 54 UV 50, in the 1/2 in. and 3/4 in. nominal outlet sizes are intended for direct connection to sprinklers.

Models UV 53, 3JS, UV 55, UV 58, in the 1 in. nominal outlet sizes are intended for direct connection to sprinklers.

Models UV 51, UV 52, UV 53, UV 54, UV 55, UV 50 UV 56, UV 58, UV 85, in the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

10 refers to Schedule 10 steel pipe.

40 refers to Schedule 40 steel pipe in accordance with NFPA 13.

1387-10 refers to BS 1387 Schedule 10 steel pipe

1387-40 refers to BS 1387 Schedule 40 steel pipe

1387-M refers to BS 1387 medium steel pipe

1387-H refers to BS 1387 heavy steel pipe

EN 10255-M refers to medium thickness steel pipe manufactured in accordance with BS EN 10255

EN 10255-H refers to heavy thickness steel pipe manufactured in accordance with BS EN 10255

4200 refers to ISO 4200 Group 1 steel pipe

4200 D refers to ISO 4200 Group 1 Type D steel pipe

4200 E refers to ISO 4200 Group 1 Type E steel pipe

3454-20 refers to JIS G3454 Schedule 20 steel pipe

3452-SPP SGP refers to JIS G3452 steel pipe.

3452 refers to JIS G3452 steel pipe.

3454-40 refers to JIS G3454 Schedule 40 steel pipe.

GB/T 21835 refers to steel pipe manufactured in according with GB/T 21835.

10255-M refers to EN 10255 M series steel pipe.

Last Updated on 2022-08-22

---

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL 认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“©2022 UL LLC.”