



Valves | Anti-Water Hammer Check Valves | **Check Valves, Anti-Water Hammer**

Model UVDC-300

Product Description

Resilient Seated Valves. The rated working pressure of the valves listed below is 300 psi (2065 kPa).

Product Specification

Model No	Valve Size		Flow Rate		Friction Loss	
	in	(mm)	gal/min	(dm ³ /min)	psi	(kPa)
UVDC-300	2	(50)	210	(795)	9.1	(63)
UVDC-300	2 1/2	(65)	300	(1135)	5.5	(38)
UVDC-300	3	(80)	460	(1740)	6.6	(45)
UVDC-300	4	(100)	795	(3010)	9.3	(64)
UVDC-300	5	(125)	1245	(4710)	7.7	(53)
UVDC-300	6	(150)	1800	(6815)	6.2	(43)
UVDC-300	8	(200)	3120	(11810)	3.0	(21)



Model No	Valve Size		Flow Rate		Friction Loss	
	in	(mm)	gal/min	(dm³/min)	psi	(kPa)
UVDC-300	10	(250)	4915	(18605)	3.0	(21)
UVDC-300	12	(300)	7050	(26685)	3.8	(26)
UVDC-300	14	(350)	8450	(31985)	3.2	(22)
UVDC-300	16	(400)	11000	(41635)	4.1	(28)

Details

Category	Check Valves, Anti-Water Hammer
Class of Work	1230 - Anti-Wtr Hammer Ck Valves
Approval Standard	FM 1230 - Anti-Water Hammer Check Valves
Certification Type	FM Approved
Listing Country	Turkiye

Company

GIACOMINI UNIVAL TESISAT
ARMATÜRLERİ
SANAYİ VE TİCARET LTD. STİ., İstanbul
Anadolu Yakası Organize Sanayi
Bölgesi, Aydınli Mah.Mermerciler Cad.
No: 10, Tuzla-İstanbul, Türkiye